

吹灌旋一体机

>>> Blowing-Filling-Capping Combiblock



产品适用范围 (Application):

适用于PET瓶包装的饮用水、碳酸饮料、果汁、茶、液态奶、液态调味品及日化品等。
It is applied for PET bottled drinking water, CSD, juice, tea, liquid milk, liquid condiment and daily health products, etc.

生产能力 (Capacity):

12000瓶/小时到44000瓶/小时
12000BRH to 44000BRH

优点

>>> Advantage

- 1 更小的占地面积
Smaller Footprint
- 2 更低的能耗
Lower Energy Consumption
- 3 更少的操作人员
Fewer Operators
- 4 更低的运行成本
Less Operation Costs

主要技术参数

>>> MAIN TECHNICAL FEATURES

型号 Model	额定能力 Capacity	最高速度 Max Speed	瓶胚尺寸 Preform Size				瓶尺寸 Bottle Size			
	500ml	≤350ml	瓶口尺寸(mm) Neck Size	瓶胚高度(mm) Preform Height	瓶胚内径(mm) Neck Inner Size	支承环直径(mm) Support Ring Diameter	圆瓶直径范围(mm) Round Bottle	瓶尺寸(对角线)(mm) Bottle Diagonal	支承环以下高度(mm) Height Under-support Ring	容量范围(L) Volume
CGXR6-24-8	12,000BPH	13,200BPH	Φ26-Φ38	≤150	Φ14-Φ26	Φ26-Φ40	Φ50-Φ116	50-116	≤320	0.2L-2.5L
CGXR8-24-8	15,000BPH	17,600BPH	Φ26-Φ38	≤150	Φ14-Φ26	Φ26-Φ40	Φ50-Φ116	50-116	≤320	0.2L-2.5L
CGXR10-32-10	20,000BPH	22,000BPH	Φ26-Φ38	≤150	Φ14-Φ26	Φ26-Φ40	Φ50-Φ116	50-116	≤320	0.2L-2.5L
CGXR12-40-15	24,000BPH	26,400BPH	Φ26-Φ38	≤150	Φ14-Φ26	Φ26-Φ40	Φ50-Φ116	50-116	≤320	0.2L-2.5L
CGXR14-50-15	28,000BPH	30,800BPH	Φ26-Φ38	≤150	Φ14-Φ26	Φ26-Φ40	Φ50-Φ116	50-116	≤320	0.2L-2.5L
CGXR16-60-18	32,000BPH	35,200BPH	Φ26-Φ38	≤150	Φ14-Φ26	Φ26-Φ40	Φ50-Φ116	50-116	≤320	0.2L-2.5L
CGXR18-60-18	36,000BPH	39,600BPH	Φ26-Φ38	≤150	Φ14-Φ26	Φ26-Φ40	Φ50-Φ116	50-116	≤320	0.2L-2.5L
CGXR20-72-22	40,000BPH	44,000BPH	Φ26-Φ38	≤150	Φ14-Φ26	Φ26-Φ40	Φ50-Φ116	50-116	≤320	0.2L-2.5L

备注：以上为水线的速度，含气饮料大约为上面的产量90%，热灌装产品大约为65%左右
Notes: Above is water bottle speed, CSD would be 90% and hot fill about 65%.



地址Add: 中国浙江省湖州市长兴国家级开发区发展大道2587号
No. 2587, Development Avenue, Changxing, Huzhou, Zhejiang Province, China
电话Tel: 0572-6559071, 021-60391126
邮箱Email: sales@demark-pet.com